

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: OTTOPUR OP 920**
- **UFI: MXF1-Y01F-100V-QR11**
- **Application of the substance / the mixture** Assembly foam
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Hermann Otto GmbH  
Krankenhausstraße 14  
D-83413 Fridolfing  
Tel.: 0049/(0)8684/908-0  
Fax.: 0049/(0)8684/908-1840
- **Further information obtainable from:**  
Tel.: 0049- (0)8684- 908- 2363 ( -4300 )  
E-Mail: alois.parzinger@otto-chemie.de
- **1.4 Emergency telephone number:**  
Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)  
Tel.: 0049/621/60-43333 (BASF Plant fire brigade)  
+44 1865 407333 (Carechem 24)

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1     H222-H229     *Extremely flammable aerosol. Pressurised container: May burst if heated.*



health hazard

Resp. Sens. 1 H334     *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*

Carc. 2     H351     *Suspected of causing cancer.*

STOT RE 2     H373     *May cause damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.*



Skin Irrit. 2     H315     *Causes skin irritation.*

Eye Irrit. 2     H319     *Causes serious eye irritation.*

Skin Sens. 1     H317     *May cause an allergic skin reaction.*

STOT SE 3     H335     *May cause respiratory irritation.*

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
*The product is classified and labelled according to the GB CLP regulation.*
- **Hazard pictograms** GHS02, GHS07, GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
*tris(2-chlorisopropyl)-phosphate*  
*diphenylmethanediisocyanate, isomeres and homologues*

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

**Trade name: OTTOPUR OP 920**

(Contd. of page 1)

ethanediol

**Hazard statements**

- H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*
- H315 *Causes skin irritation.*
- H319 *Causes serious eye irritation.*
- H334 *May cause allergy or asthma symptoms or breathing difficulties if inhaled.*
- H317 *May cause an allergic skin reaction.*
- H351 *Suspected of causing cancer.*
- H335 *May cause respiratory irritation.*
- H373 *May cause damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.*

**Precautionary statements**

- P102 *Keep out of reach of children.*
- P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
- P211 *Do not spray on an open flame or other ignition source.*
- P251 *Do not pierce or burn, even after use.*
- P271 *Use only outdoors or in a well-ventilated area.*
- P280 *Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.*
- P304+P312 *IF INHALED: Call a POISON CENTER/doctor if you feel unwell.*
- P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.*
- P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

**Additional information:**

Contains isocyanates. May produce an allergic reaction.  
As from 24 August 2023 adequate training is required before industrial or professional use.

**2.3 Other hazards**

Information according to UK REACH- Annex XVII.56

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
  - Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
  - This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type A1 according to standard EN 14387) is used.
- Important: after activation it is imperative to apply OTTOPUR OP 920 within the given tooling temperature and pot life (see technical data sheet); otherwise danger of bursting!

**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate	<25%
EINECS: 237-158-7	⚠ Acute Tox. 4, H302	
Reg.nr.: 01-2119447716-31-XXXX		

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

**Trade name: OTTOPUR OP 920**

(Contd. of page 2)

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	<25%
CAS: 9016-87-9 Reg.nr.: EG: Polymer	diphenylmethanediisocyanate, isomeres and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	<25%
CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 02-2119752517-33-0000	ethanediol ⚠ STOT RE 2, H373; ⚠ Acute Tox. 4, H302	<10%
· <b>Additional information</b> For the wording of the listed hazard phrases refer to section 16.		

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

##### · **General information**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

##### · **After inhalation**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

##### · **After skin contact**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

##### · **After eye contact**

Rinse opened eye for several minutes under running water. Then consult a doctor.

##### · **After swallowing**

Do not induce vomiting; call for medical help immediately. Show container or label.

#### · 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

After inhalation: dry throat/neck pain. Cough. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Running of the nose. CONSEQUENTIAL SYMPTOMS MAY OCCURE:

Possible inflammation of the respiratory tract. Pulmonary edema possible. Difficulty breathing. After skin contact: Tingles/irritation of the skin. After eye contact: Irritation of the eye tissue. Lachrymal flow.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

##### · **Suitable extinguishing agents**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

##### · **For safety reasons unsuitable extinguishing agents** Water with full jet.

#### · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

#### · 5.3 Advice for firefighters

##### · **Protective equipment:**

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

Trade name: OTTOPUR OP 920

(Contd. of page 3)

- **Additional information** Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Allow to solidify. Pick up mechanically.
- **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
see item 8: Personal protective equipment
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Protect from heat.  
Keep ignition sources away - Do not smoke.  
Fumes can combine with air to form an explosive mixture.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurised containers.  
Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.  
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
- 115-10-6 dimethyl ether**  
WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 766 mg/m<sup>3</sup>, 400 ppm
- 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**  
WEL Short-term value: 0.07 mg/m<sup>3</sup>  
Long-term value: 0.02 mg/m<sup>3</sup>  
Sen; as -NCO
- 107-21-1 ethanediol**  
WEL Short-term value: 104\*\* mg/m<sup>3</sup>, 40\*\* ppm  
Long-term value: 10\* 52\*\* mg/m<sup>3</sup>, 20\*\* ppm  
Sk \*particulate \*\*vapour
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

Trade name: OTTOPUR OP 920

(Contd. of page 4)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**  
The usual precautionary measures are to be adhered to when handling chemicals.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type A1 according to standard EN 14387) is used.
- **Hand protection** Protective gloves.
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.  
Recommended glove material: Butyl rubber, BR  
Recommended thickness of the material: >0,4 mm
- **Penetration time of glove material** Breakthrough time: 10 - 30 min
- **Eye/face protection** Safety glasses
- **Body protection:** Protective work clothing.

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Aerosol
- **Colour:** Different according to colouring
- **Odour:** Characteristic
- **Melting point/freezing point:** undetermined
- **Boiling point or initial boiling point and boiling range** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** Not applicable, as aerosol
- **Decomposition temperature:** Not determined.
- **pH** Not applicable.
- **Viscosity:** Not determined.
- **Solubility**
- **Water:** Hydrolized
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 5,100 hPa
- **Density and/or relative density**
- **Density at 20 °C:** 1 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapour density** Not applicable.
- **9.2 Other information**
- **Form:** Aerosol
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Information with regard to physical hazard classes**
- **Aerosols**  
Extremely flammable aerosol. Pressurised container: May burst if heated.
- **Flammable liquids** Void

GB

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

Trade name: OTTOPUR OP 920

(Contd. of page 5)

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.  
Avoid strong heating.
- **10.3 Possibility of hazardous reactions**  
Danger of receptacles bursting because of high vapour pressure when heated
- **10.5 Incompatible materials:** Strong oxidizing agents, alkalis, amines, strong acids
- **10.6 Hazardous decomposition products:** see item 5.2

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
  - **Acute toxicity** Based on available data, the classification criteria are not met.
  - **LD/LC50 values relevant for classification:**
- 
- 13674-84-5 tris(2-chlorisopropyl)-phosphate**  
Dermal LD50 >2,000 mg/kg (rat)
- 115-10-6 dimethyl ether**  
Inhalative LC50/4 h 308 mg/l (rat)
- 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**  
Oral LD50 >10,000 mg/kg (rat)  
Dermal LD50 >9,400 mg/kg (rbt)  
Inhalative LC50/4 h 0.49 mg/l (rat)
- 107-21-1 ethanediol**  
Oral LD50 1,600 mg/kg (rat)  
Dermal LD50 9,530 mg/kg (rbt)
- **Skin corrosion/irritation** Causes skin irritation.
  - **Serious eye damage/irritation** Causes serious eye irritation.
  - **Respiratory or skin sensitisation**  
Sensitive people may react strongly to minimal concentrations. We advise asthmatics and people who tend to diseases of the respiratory tracts against the contact with this product.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.
  - **Carcinogenicity** Suspected of causing cancer.
  - **STOT-single exposure** May cause respiratory irritation.
  - **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.
  - **Additional toxicological information:**
- 
- Oral Acute toxicity estimate (ATE mix) >2,000 mg/kg (rat)  
Inhalative Acute toxicity estimate (ATE mix) >5 mg/l/4h (rat)
- **11.2 Information on other hazards**
  - **Endocrine disrupting properties**
- 
- None of the ingredients is listed.

### SECTION 12: Ecological information

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

Trade name: OTTOPUR OP 920

(Contd. of page 6)

- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Observe local by-laws.  
Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.
- **Uncleaned packaging:**
- **Recommendation:**  
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG, IATA** AEROSOLS
- **14.3 Transport hazard class(es)**
- **ADR**



- **Class** 2 5F Gases.
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2 Gases.
- **Label** 2.1
- **14.4 Packing group**
- **ADR, IMDG, IATA** Void
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Gases.
- **Hazard identification number (Kemler code):** -
- **EMS Number:** F-D, S-U

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

Trade name: OTTOPUR OP 920

(Contd. of page 7)

- **Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
- **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.  
For AEROSOLS with a capacity above 1 litre:  
Segregation as for the appropriate subdivision of class 2.  
For WASTE AEROSOLS:  
Segregation as for the appropriate subdivision of class 2.
- **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
- **Transport/Additional information:**
- **ADR**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **Transport category** 2
- **Tunnel restriction code** D
- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations**
- **Information about limitation of use:**  
Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Details of international registration status:**  
**Listed on or in accordance with the following inventories:**  
UK REACH - Europe listed  
AICS - Australia not listed  
DSL - Canada not listed  
IECSC - China not listed  
ENCS - Japan not listed  
NZIoC - New Zealand not listed  
PICCS - Philippines not listed  
ECL - Korea not listed  
TSCA - USA not listed  
TCSI - Taiwan not listed

(Contd. on page 9)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 15.02.2023

Version 4 (replaces version 3)

Revision: 15.02.2023

Trade name: OTTOPUR OP 920

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

H220 Extremely flammable gas.  
 H280 Contains gas under pressure; may explode if heated.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.  
 H351 Suspected of causing cancer.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 EUH204 Contains isocyanates. May produce an allergic reaction.

· **Department issuing SDS:** Tel.: 0049- (0)8684- 908- 2363

· **Contact:** Tel.: 0049- (0)8684- 908- 2363 ( -4300 )

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· **\* Data compared to the previous version altered.**