Revision: 11.11.2024

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 5 (replaces version 4)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: OTTO Primer 1105
- · UFI: HFG1-005T-V00U-QSHE
- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0

Tel.: 0049/(0)8684/908-0 Fax.: 0049/(0)8684/908-1840

· Further information obtainable from:

Tel.: 0049- (0)8684- 908- 2363 (-4300) E-Mail: alois.parzinger@otto-chemie.de • 1.4 Emergency telephone number:

Tel.: 0049- (0) 89- 192 40 (emergency telephone no.) Tel.: 0049/621/60-43333 (BASF Plant fire brigade)

+44 1865 407333 (Carechem 24)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS05 GHS07





GHS08

· **Signal word** Danger

· Hazard-determining components of labelling:

xylene (mix) butanol ethylbenzene

butanone

Hazard statements

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled. H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

(Contd. of page 1)

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms









GHS02 GHS05 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

xylene (mix) butanol ethylbenzene butanone

Hazard statements

H318 Causes serious eye damage. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves / eye protection / face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.

· vPvB: Not applicable.

· Determination of endocrine-disrupting properties

This product does not contain components that are endocrine disruptors according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

CAS: 78-93-3

· Description: Solvent mixture with additives.

Dangerous components:

H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335

Reg.nr.: 01-2119488216-32-0000

butanone

EINECS: 201-159-0 Reg.nr.: 01-2119457290-43

♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066

(Contd. on page 3)

<50%

<25%

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

(Contd. of page 2)

Reg.nr.: 01-2119489370-35 Flam. Liq. 2, H225; \$ \$101 RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412

Reg.nr.: 01-2119484630-38 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336

CAS: 108-88-3 toluene <1%

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache Dizziness Dizziness Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents Water with full jet.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation

Keep away from ignition sources

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

(Contd. of page 3)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

see item 8: Personal protective equipment

· Information about fire - and explosion protection:

Protect against electrostatic charges.

Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear ofignition sources.

Highly volatile, flammable constituents are released during processing.

Flammable gas-air mixtures may form in empty receptacles.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Prevent any seepage into the ground.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm

Sk

71-36-3 butanol

WEL Short-term value: 154 mg/m³, 50 ppm

Sk

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

Sk

Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

(Contd. on page 5)

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

(Contd. of page 4)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

Respiratory protection:

Use suitable respiratory protective device when high concentrations are present.

- Hand protection Protective gloves.
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended glove material: Butyl rubber, BR Recommended thickness of the material: >0,4 mm

- · Penetration time of glove material Breakthrough time: 10 30 min
- · Eye/face protection Tightly sealed goggles. · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Colourless · Odour: Characteristic -50 °C

Melting point/freezing point:

· Boiling point or initial boiling point and

boiling range 110 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

· Lower: 1.7 Vol % · Upper: 11.5 Vol % 7°C · Flash point: 505 °C Auto-ignition temperature:

Decomposition temperature: Not determined. Not applicable. · pH Viscosity at 20 °C: 300 mPas

Solubility

· Water: Not determined.

· Partition coefficient n-octanol/water (log

Not determined. value)

Vapour pressure at 20 °C: 8 hPa

Density and/or relative density

Density at 20 °C: 0.94 q/cm3 Not determined. · Relative density Not determined. · Vapour density Particle characteristics undetermined

· 9.2 Other information

· Form: Fluid

Product is not selfigniting. · Ignition temperature:

Product is not explosive. However, formation of · Explosive properties:

explosive air/vapour mixtures are possible.

(Contd. on page 6)

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

(Contd. of page 5)

· Information with regard to physical hazard classes

· Aerosols Void

· Flammable liquids Highly flammable liquid and vapour.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Avoid strong heating.

· 10.3 Possibility of hazardous reactions

Danger of receptacles bursting because of high vapour pressure when heated

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised

- · 10.5 Incompatible materials: Strong oxidizing agents, alkalis, amines, strong acides
- · 10.6 Hazardous decomposition products: see item 5.2

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.
- · LD/LC50 values relevant for classification:

1330-20-7 xylene (mix)

Oral LD50 3,523 mg/kg (rat)

Dermal LD50 >4,200 mg/kg (rabbit)

Inhalative LC50/4 h 29.091 mg/l (rat)

78-93-3 butanone

Oral LD50 2,193 mg/kg (rat) (OECD 423)

Dermal LD50 >8,100 mg/kg (rabbit)

71-36-3 butanol

Oral LD50 790 mg/kg (rat)
Dermal LD50 3,400 mg/kg (rabbit)
Inhalative LC50/4 h 8,000 mg/l (rat)

108-88-3 toluene

Oral LD50 5,580 mg/kg (rat)
Dermal LD50 12,400 mg/kg (rab)

Inhalative LC50/4 h 28 mg/l (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Oral Acute toxicity estimate (ATE mix) >5,000 mg/kg

Dermal Acute toxicity estimate (ATE mix) 2,164 mg/kg

Inhalative Acute toxicity estimate (ATE mix) 13.4 mg/l/4h

(Contd. on page 7)

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

· 11.2 Information on other hazards

(Contd. of page 6)

- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation Liquid residues must be specially treated adhering to official regulations.
- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA

UN1993

· 14.2 UN proper shipping name

· ADR

1993 FLAMMABLE LIQUID, N.O.S. (XYLENES, ETHYL METHYL KETONE (METHYL ETHYL

KETONE))

· IMDG, IATA FLAMMABLE LIQUID, N.O.S. (XYLENES, ETHYL METHYL KETONE (METHYL ETHYL KETONE))

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 8)

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

(Contd. of page 7)

· 14.4 Packing group

· ADR, IMDG, IATA

II

· 14.5 Environmental hazards:

No · Marine pollutant:

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 33 F-E,S-E · EMS Number: · Stowage Category

· 14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category · Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E2

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S.

(XYLENES, ETHYL METHYL KETONE (METHYL

ETHYL KETONE)), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 9)

Printing date 11.11.2024 Version 5 (replaces version 4) Revision: 11.11.2024

Trade name: OTTO Primer 1105

· Regulation (EC) No 273/2004 on drug precursors

(Contd. of page 8)

78-93-3 butanone: 3 108-88-3 toluene: 3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the

Community and third countries in drug precursors

78-93-3 butanone: 3 108-88-3 toluene: 3 • National regulations

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Details of international registration status:

Listed on or in accordance with the following inventories:

PICCS - Philippines not listed
TCSI - Taiwan listed
UK REACH - Europe listed
AICS - Australia listed
DSL- Canada listed
IECSC - China listed
ECL - Korea listed

ECL - Korea listed
TSCA - USA listed
ENCS - Japan listed
NZIOC - New Zealand not listed

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Tel.: 0049- (0)8684- 908- 2363
- · Contact: Tel.: 0049- (0)8684- 908- 2363 (-4300)
- · Date of previous version: 03.01.2022
- · Version number of previous version: 4
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 5 (replaces version 4)

Trade name: OTTO Primer 1105

(Contd. of page 9)

Revision: 11.11.2024

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.