Revision: 11.11.2024

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 7 (replaces version 6)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: OTTO Primer 1216

· **UFI**: 4X20-D07J-K00X-AQ2Q

· Application of the substance / the mixture Priming

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0

Tel.: 0049/(0)8684/908-0 Fax.: 0049/(0)8684/908-1840

· Further information obtainable from:

Tel.: 0049- (0)8684- 908- 2363 (-4300) E-Mail: alois.parzinger@otto-chemie.de • 1.4 Emergency telephone number:

Tel.: 0049- (0) 89- 192 40 (emergency telephone no.) Tel.: 0049/621/60-43333 (BASF Plant fire brigade)

+44 1865 407333 (Carechem 24)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms











GHS02 GHS05 GHS07 GHS08 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), light alkylate

tetra-n-butoxytitanium

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eve damage.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

(Contd. on page 2)

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

· Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms











GHS05 GHS07 GHS08

· Signal word Danger

Hazard-determining components of labelling:

Naphtha (petroleum), light alkylate

tetra-n-butoxytitanium

Hazard statements

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P280 Wear protective gloves / eye protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · vPvB: Not applicable.

Determination of endocrine-disrupting properties

This product does not contain components that are endocrine disruptors according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Solvent mixture with additives.

Dangerous components:

50-100% CAS: 64741-66-8 Naphtha (petroleum), light alkylate

CAS: 5593-70-4 tetra-n-butoxytitanium <10%

CAS: 78-10-4 <5% tetraethyl silicate

EINECS: 201-083-8

(Contd. on page 3)

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

(Contd. of page 2)

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Dizziness

Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents Water with full jet.
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

(Contd. of page 3)

see item 8: Personal protective equipment

Information about fire - and explosion protection:

Protect against electrostatic charges.

Traces of flammable substances may collect in the steam chamber of enclosed systems. Keep clear ofignition sources.

Highly volatile, flammable constituents are released during processing.

Flammable gas-air mixtures may form in empty receptacles.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Prevent any seepage into the ground.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

78-10-4 tetraethyl silicate

WEL Long-term value: 44 mg/m³, 5 ppm

· DNELs

64741-66-8 Naphtha (petroleum), light alkylate

Dermal Worker, systemic (long term) 773 mg/kg/Tag (rat)

Consumer, systemic (long term) 699 mg/kg/Tag (rat)

Inhalative Worker, systemic (long term) 2,035 mg/m3 (rat)

Consumer, systemic (long term) 608 nmg/m3 (rat)

- · CAS No. Designation of material % Type Value Unit
- Additional Occupational Exposure Limit Values for possible hazards during processing:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures

Do not inhale gases / fumes / aerosols.

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Pregnant women should strictly avoid inhalation or skin contact.

· Respiratory protection:

Use suitable respiratory protective device when high concentrations are present.

- · Hand protection Protective gloves.
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended glove material: Butyl rubber, BR

Recommended thickness of the material: >0,4 mm

- · Penetration time of glove material Breakthrough time: 10 30 min
- · Eye/face protection Tightly sealed goggles.

(Contd. on page 5)

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

· Body protection: Protective work clothing.

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid Yellowish · Colour: · Odour: Characteristic • Melting point/freezing point: undetermined

· Boiling point or initial boiling point and

boiling range 116-142 °C (bei 1013 hPa) · Flammability Highly flammable.

· Lower and upper explosion limit

0.7 Vol % · Lower: · Upper: 7 Vol %

2 °C (ISO 13736) Flash point: 380 °C (EN 14522) Auto-ignition temperature: · Decomposition temperature: Not determined. · pH Not determined. Viscosity at 20 °C: 1 mm2/s (DIN 51562-1)

· Solubility · Water:

· Partition coefficient n-octanol/water (log

Not determined. value) · Vapour pressure at 25 °C: 50 hPa (EG-RL.A.4)

121.5 hPa · Vapour pressure at 50 °C:

Density and/or relative density

0.76 g/cm³ (DIN 51757) · Density at 20 °C: Not determined. · Relative density

Not determined. · Vapour density · Particle characteristics undetermined

· 9.2 Other information

· Form: Fluid

· Ignition temperature: Product is not selfigniting.

Product is not explosive. However, formation of · Explosive properties: explosive air/vapour mixtures are possible.

Not determined.

· Information with regard to physical hazard

classes · Aerosols Void

· Flammable liquids Highly flammable liquid and vapour.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Avoid strong heating.

· 10.3 Possibility of hazardous reactions

Danger of receptacles bursting because of high vapour pressure when heated

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised

· 10.5 Incompatible materials: Strong oxidizing agents, alkalis, amines, strong acides

(Contd. on page 6)

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

· 10.6 Hazardous decomposition products: see item 5.2

(Contd. of page 5)

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

64741-66-8 Naphtha (petroleum), light alkylate

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rab)

Inhalative LC50/4 h >20 mg/l (rat)

5593-70-4 tetra-n-butoxytitanium

Oral LD50 3,122 mg/kg (rat)

78-10-4 tetraethyl silicate

Oral LD50 6,270 mg/kg (rat)
Dermal LD50 5,860 mg/kg (rab)

Inhalative LC50/4 h 10 mg/l (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.
- · Additional toxicological information:

Oral Acute toxicity estimate (ATE mix) >5,000 mg/kg (ATE)

- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

This product does not contain components that are endocrine disruptors according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

The material is harmful to the environment.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

ab

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Liquid residues must be specially treated adhering to official regulations.
- Uncleaned packaging:
- Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1993

· 14.2 UN proper shipping name

· **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (Naphtha

(petroleum), light alkylate, tetra-n-butoxytitanium),

ENVIRONMENTALLY HAZARDOUS FLAMMABLE LIQUID, N.O.S. (Naphtha

(petroleum), light alkylate, tetra-n-butoxytitanium),

MARINE POLLUTANT

· IATA FLAMMABLE LIQUID, N.O.S. (Naphtha

(petroleum), light alkylate, tetra-n-butoxytitanium)

· 14.3 Transport hazard class(es)

· ADR

· IMDG





· Class 3 (F1) Flammable liquids.

· Label

· IMDG





· Class 3 Flammable liquids.

· Label

·IATA



· Class 3 Flammable liquids.

· Label 3 · 14.4 Packing group

· ADR, IMDG, IATA

• **14.5 Environmental hazards:** Product contains environmentally hazardous

substances: Naphtha (petroleum), light alkylate

Marine pollutant: Symbol (fish and tree)
 Special marking (ADR): Symbol (fish and tree)
 14.6 Special precautions for user
 Warning: Flammable liquids.

Hazard identification number (Kemler code): 33

EMS Number: F-E,S-E

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

· Stowage Category B

• 14.7 Maritime transport in bulk according to
IMO instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category 2 · Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml UN 1993 FLAMMABLE LIQUID, N.O.S. (NAPHTHA

(PETROLEUM), LIGHT ALKYLATE, TETRA-N-BUTOXYTITANIUM), 3, II, ENVIRONMENTALLY

HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

UN "Model Regulation":

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 9)

Printing date 11.11.2024 Version 7 (replaces version 6) Revision: 11.11.2024

Trade name: OTTO Primer 1216

(Contd. of page 8)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations

· Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Details of international registration status:

Listed on or in accordance with the following inventories:

UK REACH - Europe listed
ENCS - Japan listed
TSCA - USA listed
AICS - Australia listed
DSL- Canada listed

PICCS - Philippines listed
ECL - Korea listed
IECSC - China listed
TCSI - Taiwan listed
NZIOC - New Zealand listed

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Tel.: 0049- (0)8684- 908- 2363

· Contact: Tel.: 0049- (0)8684- 908- 2363 (-4300)

Date of previous version: 02.01.2023

Version number of previous version: 6

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

(Contd. on page 10)

Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024

Version 7 (replaces version 6)

Trade name: OTTO Primer 1216

(Contd. of page 9)

Revision: 11.11.2024

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

* Data compared to the previous version altered.