

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.10.2024

Version 6 (replaces version 2)

Revision: 31.10.2024



SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** **OTTOSEAL S 80**
- **Application of the substance / the mixture** *Silicone sealant*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Hermann Otto GmbH
 Krankenhausstraße 14
 D-83413 Fridolfing
 Tel.: 0049/(0)8684/908-0
 Fax.: 0049/(0)8684/908-1840*
- **Further information obtainable from:**
*Tel.: 0049- (0)8684- 908- 2363 (-4300)
 E-Mail: alois.parzinger@otto-chemie.de*
- **1.4 Emergency telephone number:**
*Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)
 +44 1865 407333 (Carechem 24)*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified, according to the GB CLP regulation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** *Void*
- **Hazard pictograms** *Void*
- **Signal word** *Void*
- **Hazard statements** *Void*
- **Additional information:**
*Ensure good ventilation during application and curing.
 Contains the active agent biocide 2-octyl-2H-isothiazol-3-one to protect against mould infestation.
 Keep out of the reach of children.
 Avoid contact with skin.
 EUH208 Contains trimethoxyvinylsilane, N-(3-(trimethoxysilyl)propyl)ethylenediamine, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
 EUH210 Safety data sheet available on request.*
- **2.3 Other hazards**
During processing and curing of the material, chemical substances are released into the air (see point 11). Therefore, ensure good room ventilation and, if necessary, exhaust ventilation.
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **Determination of endocrine-disrupting properties**
This product does not contain components that are endocrine disruptors according to UK REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
 - **Description:** *Polydimethylsiloxane, filler, auxiliaries, alkoxysilane crosslinker*
 - **Dangerous components:**
- | | | |
|---|---|-------|
| CAS: 2768-02-7 | <i>trimethoxyvinylsilane</i> | <2.5% |
| EINECS: 220-449-8 |  <i>Flam. Liq. 3, H226;</i>  <i>Acute Tox. 4, H332;</i> <i>Skin Sens.</i> | |
| Reg.nr.: 01-2119513215-52-xxxx 1B, H317 | | |

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.10.2024

Version 6 (replaces version 2)

Revision: 31.10.2024

Trade name: OTTOSEAL S 80

(Contd. of page 1)

CAS: 1760-24-3

N-(3-(trimethoxysilyl)propyl)ethylenediamine

<1%

EINECS: 217-164-6

☠ Eye Dam. 1, H318; ☠ Aquatic Chronic 2, H411;

Reg.nr.: 01-2119970215-39-xxxx ☠ Acute Tox. 4, H332; Skin Sens. 1, H317

CAS: 26530-20-1

2-octyl-2H-isothiazol-3-one

<0.1%

EINECS: 247-761-7

☠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; ☠ Skin Corr. 1, H314; Eye Dam. 1, H318;

☠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ☠ Skin Sens. 1A, H317, EUH071

ATE: LD50 oral: 125 mg/kg

LD50 dermal: 311 mg/kg

LC50/4 h inhalative: 0.27 mg/l

Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %

Additional information

For the wording of the listed hazard phrases refer to section 16.

Particulate raw materials with risk of inhalation are inextricably bound in the product and therefore does not trigger classification of the product for inhalation hazards. Due to the product's physical properties, particulate inhalation exposure is not possible.

SECTION 4: First aid measures**4.1 Description of first aid measures****After inhalation**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters**Protective equipment:**

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.10.2024

Version 6 (replaces version 2)

Revision: 31.10.2024

Trade name: OTTOSEAL S 80

(Contd. of page 2)

- **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
see item 8: Personal protective equipment
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
- **CAS No. Designation of material % Type Value Unit**
- **Additional Occupational Exposure Limit Values for possible hazards during processing:**
- **67-56-1 methanol**
WEL Short-term value: 333 mg/m³, 250 ppm
Long-term value: 266 mg/m³, 200 ppm
Sk
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type ABEK according to standard EN 14387) is used.
- **Hand protection** Protective gloves.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Recommended glove types: nitrile rubber
Recommended thickness of the material: >0,4 mm
- **Penetration time of glove material** Breakthrough time: 10 - 30 min
- **Eye/face protection** Safety glasses
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Melting point/freezing point:** undetermined

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.10.2024

Version 6 (replaces version 2)

Revision: 31.10.2024

Trade name: OTTOSEAL S 80

(Contd. of page 3)

- **Boiling point or initial boiling point and boiling range** undetermined
- **Lower and upper explosion limit**
- **Lower:** not applicable
- **Upper:** not applicable
- **Flash point:** Not applicable (test methods for flash point not valid for pasty substances and highly viscous liquids)
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:** Not determined.
- **Solubility**
- **Water:** Insoluble
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure:** Not determined.
- **Density and/or relative density**
- **Density:** see technical data sheet
- **Relative density** Not determined.
- **Vapour density** Not applicable.
- **Particle characteristics** undetermined
- **9.2 Other information**
- **Form:** pasty
- **Ignition temperature:** Not determined.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Information with regard to physical hazard classes**
- **Aerosols** Void
- **Flammable liquids** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Avoid strong heating.
- **10.3 Possibility of hazardous reactions**
Contact with humidity, water and protic agents produces methanol.
- **10.6 Hazardous decomposition products:**
see item 5.2
Tests on representative products have shown that above temperatures of 150° C small quantities of formaldehyde are split off.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.
 - **LD/LC50 values relevant for classification:**
-
- 2768-02-7 trimethoxyvinylsilane**
- | | | |
|------------|----------|-------------------|
| Oral | LD50 | 7,100 mg/kg (rat) |
| Dermal | LD50 | 3,200 mg/kg (rab) |
| Inhalative | LC50/4 h | 16.8 mg/l (rat) |

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.10.2024

Version 6 (replaces version 2)

Revision: 31.10.2024

Trade name: OTTOSEAL S 80

(Contd. of page 4)

1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine

Oral LD50 2,995 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rab)

26530-20-1 2-octyl-2H-isothiazol-3-one

Oral LD50 125 mg/kg (ATE)

Dermal LD50 311 mg/kg (ATE)

Inhalative LC50/4 h 0.27 mg/l (ATE)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
dermal: not sensitizing
Source: Conclusion by analogy
Test report according to OECD Guideline 406 (Guinea Pigs)
Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Other information (about experimental toxicology):**
Product hydrolyses under formation of methanol (CAS no. 67-56-1). Methanol is toxic by inhalation, in contact with skin and if swallowed. Methanol causes damage to organs. Methanol is highly flammable. Inhalation of aerosol spray may damage health.
- **Additional toxicological information:**

26530-20-1 2-octyl-2H-isothiazol-3-one

Oral Acute toxicity estimate (ATE mix) 125 mg/kg (rat)

Dermal Acute toxicity estimate (ATE mix) 311 mg/kg (rat)

- **11.2 Information on other hazards**
- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.2 Persistence and degradability**
- **Other information:** Product is not biodegradable.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Observe local by-laws.
Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.10.2024

Version 6 (replaces version 2)

Revision: 31.10.2024

Trade name: OTTOSEAL S 80

(Contd. of page 6)

- **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**
None of the ingredients is listed.
- **National regulations**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **Details of international registration status:**
Listed on or in accordance with the following inventories:
 - UK REACH - Europe listed
 - AICS - Australia not listed
 - ENCS - Japan not listed
 - ECL - Korea listed
 - PICCS - Philippines not listed
 - TSCA - USA listed
 - TCSI - Taiwan not listed
 - DSL - Canada not listed
 - NZIoC - New Zealand not listed
 - IECSC - China listed
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

- **Relevant phrases**
 - H226 Flammable liquid and vapour.
 - H301 Toxic if swallowed.
 - H311 Toxic in contact with skin.
 - H314 Causes severe skin burns and eye damage.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H330 Fatal if inhaled.
 - H332 Harmful if inhaled.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH071 Corrosive to the respiratory tract.
- **Department issuing SDS:** Tel.: 0049- (0)8684- 908- 2363
- **Contact:** Tel.: 0049- (0)8684- 908- 2363 (-4300)
- **Date of previous version:** 08.12.2022
- **Version number of previous version:** 2
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - ATE: Acute toxicity estimate values
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 3: Acute toxicity – Category 3
 - Acute Tox. 2: Acute toxicity – Category 2
 - Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 31.10.2024

Version 6 (replaces version 2)

Revision: 31.10.2024

Trade name: OTTOSEAL S 80

(Contd. of page 7)

Skin Corr. 1: Skin corrosion/irritation – Category 1
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
· * **Data compared to the previous version altered.**

gb