

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2023

Version 5 (replaces version 4)

Revision: 09.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking


- **1.1 Product identifier**
- **Trade name:** **OTTOSEAL S 80**
- **Application of the substance / the mixture** *Silicone sealant*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
*Hermann Otto GmbH
 Krankenhausstraße 14
 D-83413 Fridolfing
 Tel.: 0049/(0)8684/908-0
 Fax.: 0049/(0)8684/908-1840*
- **Further information obtainable from:**
*Tel.: 0049- (0)8684- 908- 2363 (-4300)
 E-Mail: alois.parzinger@otto-chemie.de*
- **1.4 Emergency telephone number:**
*+44 1865 407333 (Carechem 24)
 Tel.: 0049- (0) 89- 192 40 (emergency telephone no.)*

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified, according to the GB CLP regulation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** *Void*
- **Hazard pictograms** *Void*
- **Signal word** *Void*
- **Hazard statements** *Void*
- **Additional information:**
*Ensure good ventilation during application and curing.
 Contains the active agent biocide 2-octyl-2H-isothiazol-3-one to protect against mould infestation.
 Keep out of the reach of children.
 Avoid contact with skin.
 Contains trimethoxyvinylsilane, N-(3-(trimethoxysilyl)propyl)ethylenediamine, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
 Safety data sheet available on request.*
- **2.3 Other hazards**
During the application and curing process of the material chemicals are released as vapour (see item 11). Therefore ensure good ventilation or exhaustion if necessary.
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** *Polydimethylsiloxane, filler, auxiliaries, alkoxysilane crosslinker*
- **Dangerous components:**

Aminofunktionelles Oligosiloxan
 *Skin Irrit. 2, H315; Eye Irrit. 2, H319*

<2.5%

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2023

Version 5 (replaces version 4)

Revision: 09.01.2023

Trade name: OTTOSEAL S 80

(Contd. of page 1)

CAS: 2768-02-7	trimethoxyvinylsilane	<2.5%
EINECS: 220-449-8	⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Skin Sens. 1B, H317	
Reg.nr.: 01-2119513215-52-xxxx	Specific concentration limit: Skin Sens. 1B; H317: C ≥ 5 %	
CAS: 1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	<1%
EINECS: 217-164-6	⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317	
Reg.nr.: 01-2119970215-39-xxxx	Specific concentration limits: Eye Irrit. 2; H319: C ≥ 2.5 % Skin Sens. 1; H317: C ≥ 6 %	
CAS: 870-08-6	dioctyltin oxide	<1%
EINECS: 212-791-1	⚠ STOT SE 2, H371	
CAS: 26530-20-1	2-octyl-2H-isothiazol-3-one	<0.1%
EINECS: 247-761-7	⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317, EUH071	
	ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

· 5.3 Advice for firefighters

· Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2023

Version 5 (replaces version 4)

Revision: 09.01.2023

Trade name: OTTOSEAL S 80

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
see item 8: Personal protective equipment
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
- **CAS No. Designation of material % Type Value Unit**
- **Additional Occupational Exposure Limit Values for possible hazards during processing:**
- **67-56-1 methanol**
WEL Short-term value: 333 mg/m³, 250 ppm
Long-term value: 266 mg/m³, 200 ppm
Sk
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
The usual precautionary measures are to be adhered to when handling chemicals.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type ABEK according to standard EN 14387) is used.
- **Hand protection** Protective gloves.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
Recommended glove types: nitrile rubber
Recommended thickness of the material: >0,4 mm
- **Penetration time of glove material** Breakthrough time: 10 - 30 min
- **Eye/face protection** Safety glasses
- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Solid.
- **Colour:** According to product specification
- **Odour:** Characteristic

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2023

Version 5 (replaces version 4)

Revision: 09.01.2023

Trade name: OTTOSEAL S 80

(Contd. of page 3)

- **Melting point/freezing point:** undetermined
- **Boiling point or initial boiling point and boiling range** undetermined
- **Lower and upper explosion limit**
- **Lower:** not applicable
- **Upper:** not applicable
- **Flash point:** undetermined
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:** Not determined.
- **Solubility**
- **Water:** Insoluble
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure:** Not determined.
- **Density and/or relative density**
- **Density:** see technical datasheet
- **Relative density** Not determined.
- **Vapour density** Not applicable.
- **9.2 Other information**
- **Form:** pasty
- **Auto-ignition temperature:** Not determined.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Information with regard to physical hazard classes**
- **Aerosols** Void
- **Flammable liquids** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
Avoid strong heating.
- **10.6 Hazardous decomposition products:**
Tests on representative products have shown that above temperatures of 150° C small quantities of formaldehyde are split off.
see item 5.2

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.
 - **LD/LC50 values relevant for classification:**
-
- 2768-02-7 trimethoxyvinylsilane**
- Oral LD50 7,100 mg/kg (rat)
Dermal LD50 3,200 mg/kg (rab)
Inhalative LC50/4 h 16.8 mg/l (rat)
- 1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**
- Oral LD50 2,995 mg/kg (rat)
Dermal LD50 >2,000 mg/kg (rab)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2023

Version 5 (replaces version 4)

Revision: 09.01.2023

Trade name: OTTOSEAL S 80

(Contd. of page 4)

870-08-6 dioctyltin oxide

Oral LD50 2,500 mg/kg (rat)

26530-20-1 2-octyl-2H-isothiazol-3-one

Oral LD50 125 mg/kg (ATE)

Dermal LD50 311 mg/kg (ATE)

Inhalative LC50/4 h 0.27 mg/l (ATE)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**

dermal: not sensitizing

Source: test report OECD 406

Based on available data, the classification criteria are not met.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

· **Other information (about experimental toxicology):**

Product hydrolyses under formation of methanol (CAS no. 67-56-1). Methanol is toxic by inhalation, in contact with skin and if swallowed. Methanol causes damage to organs. Methanol is highly flammable. Inhalation of aerosol spray may damage health.

· **Additional toxicological information:****26530-20-1 2-octyl-2H-isothiazol-3-one**

Oral Acute toxicity estimate (ATE mix) 125 mg/kg (rat)

Dermal Acute toxicity estimate (ATE mix) 311 mg/kg (rat)

· **11.2 Information on other hazards**· **Endocrine disrupting properties**

870-08-6 dioctyltin oxide: List II

SECTION 12: Ecological information

- **12.2 Persistence and degradability**
- **Other information:** Product is not biodegradable.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
- For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
- Do not allow product to reach ground water, water course or sewage system.
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
- Observe local by-laws.
- Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.01.2023

Version 5 (replaces version 4)

Revision: 09.01.2023

Trade name: **OTTOSEAL S 80**

(Contd. of page 6)

H301 Toxic if swallowed.
 H311 Toxic in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H330 Fatal if inhaled.
 H332 Harmful if inhaled.
 H371 May cause damage to organs.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 EUH071 Corrosive to the respiratory tract.

· **Department issuing SDS:** Tel.: 0049- (0)8684- 908- 2363

· **Contact:** Tel.: 0049- (0)8684- 908- 2363 (-4300)

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 2: Specific target organ toxicity (single exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· * **Data compared to the previous version altered.**