


OTTOSEAL[®] S 94



		0757
Hermann Otto GmbH Krankenhausstr. 14, 83413 Fridolfing, Germany 2014 OC0094B		
EN 15651 - 1, EN 15651 - 2 EN 15651 - 4 1 component silicone sealant, neutral curing for application in the facade for glazing for pedestrian walkways - Type F EXT-INT CC, G CC, PW INT - Conditioning: Process A - Carrier material: Glass - Pre-treatment: OTTO Cleanprimer 1226		
1/2/4-1	Fire behaviour	E
1/2/4-2	Release of chemicals hazardous to health and/or the environment	NPD
Water- and airtightness		
1/2-3	Stability under load	≤ 3 mm
1/2-4	Volume loss	≤ 10 %
4-4	Volume loss	≤ 15 %
1-5	Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	NF
1/2-7	Tensile properties / secant modulus in cold climate (at -30°C)	≤ 0,9 MPa
1/2-8	Tensile properties under pretensioning in a cold climate (at -30°C)	NF
2-10	Adhesive/stress expansion action after the effects of heat, water and artificial light	NF
2-11	Resilience	≥ 60%
4-13	Tensile behaviour under pretensioning	NF
4-14	Tearing strength	NF
1/2/4-20	Durability - adhesive/stress expansion at different temperatures	NF