# **OTTOSEAL®**

Sustainability data sheet

# Inspections/authorisations



French VOC-emission class A+

• Environmental Product Declarations (EPD)

Declaration number: EPD-DBC-20220180-IBF1-EN

# Building certification system

QNG - Quality Seal for Sustainable Buildings

Version 1.3

Criterion Avoiding harmful substances in building materials

Overview table 4. Adhesives and sealants - line 4.1

Building product group Adhesives and sealants (acrylates and silicones) used on site indoors

Product documentation and declaration of contained SVHC > 0.1 % and chlorinated Requirements

paraffins ≤0.1% and declaration of biocidal active substances in silicones

Classification Meets the requirements, as declaration of contained SVHC > 0.1 % and chlorinated

paraffins ≤0.1 % and declaration of biocidal active substances in silicones.

QNG - Quality Seal for Sustainable Buildings

Version 1.3

Criterion Avoiding harmful substances in building materials

Overview table 13. Building products for building services installations - line 13.2

**Building product group** Internal and external fire barriers; fire protection filler compounds, fire protection coatings for

cables and fire protection silicones

Requirements Product documentation and declaration of contained SVHC > 0.1 % and chlorinated paraffins,

TCEP, PBB and PBDE ≤ 0.1 %

Classification Meets the requirements, as declaration of contained SVHC > 0.1 % and chlorinated

paraffins, TCEP, PBB und PBDE ≤0.1%.

Sustainability data sheet OTTOSEAL® S54 version: 2gb (13.03.2024 08:09 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY

Tel.:+49 8684-908-0 · Fax: +49 8684-12-60 e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com



### DGNB – Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2023

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 13

**Product type** Adhesive for air tightness of facades inside and outside: e.g. PU, PU Hybrid, MS Polymer, SMP,

acrylate, silicone.

Requirements Quality category 1 (low) <0.1% halogenated propellant and bonus points SVHC ≤0.1%

Quality category 2 <0.1 % halogenated propellant and bonus points SVHC ≤0.1 % Quality category 3 Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and

halogenated propellant < 0.1% and EMICODE® EC 1 PLUS or

VOC <1% and bonus points SVHC ≤0.1%

Quality category 4 (high) Chlorinated paraffins (SCCPs + MCCPs + LCCPs) < 0.1 % and

halogenated propellant < 0.1 % and EMICODE® EC 1 PLUS or

VOC <1% and bonus points SVHC ≤0.1%

Classification Fulfills quality category 4 requirements with chlorinated paraffins (SCCPs + MCCPs +

LCCPs) < 0.1 % and halogenated propellant < 0.1 % and VOC < 1 % und SVHC ≤ 0.1 %.

### DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2023

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 42

Product type Technical fire protection, bonding or sealing in interiors, PU assembly adhesives: fireproofing

primers; fireproofing coatings for cables, fireproofing silicones, PU assembly adhesives for

insulating materials (EPS, XPS, PUR)

Requirements Quality category 1 (low)

Quality category 2 -

Quality category 3 Chlorinated paraffins (SCCPs + MCCPs + LCCPs) < 0.1 % and

SVHC ≤ 0.1 %

Quality category 4 (high) Chlorinated paraffins (SCCPs + MCCPs + LCCPs) < 0.1 % and

SVHC ≤ 0.1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins (SCCPs + MCCPs +

LCCPs) < 0.1 % and SVHC < 0.1 %.

## DGNB - Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2018

**Criterion** ENV 1.2 Risks for the local environment

Criteria matrix line no. 12

**Product type**Sealants, sealant compounds, adhesives for punctiform and linear bonding of interior

components and ventilation ducts within buildings. This refers to acrylate sealants/adhesives,

silicone sealants and SMP (hybrid sealants).

Requirements Quality category 1 (low)

Quality category 2 No chlorinated paraffins declared in the SDS

Quality category 3 Chlorinated paraffins < 0.1 %

Quality category 4 (high) Chlorinated paraffins < 0.1 %, solvents < 1 % and

PAH plasticisers < 0.1 %

Classification Fulfills quality category 4 requirements with chlorinated paraffins <0.1 %, solvents <1 %

and PAH plasticisers < 0.1 %.

Sustainability data sheet OTTOSEAL® S54 Page 2 version: 2gb (13.03.2024 08:09 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com

SEALING & BONDING

### DGNB – Deutsche Gesellschaft für Nachhaltiges Bauen (German Sustainable Building Council)

Version 2018

Criterion ENV 1.2 Risks for the local environment

Criteria matrix line no. 42

Technical fire protection, bonding or sealing in interiors, PU assembly adhesives: fireproofing **Product type** 

primers; fireproofing coatings for cables, fireproofing silicones, PU assembly adhesives for

insulating materials (EPS, XPS, PUR).

Quality category 1 (low) Requirements

Quality category 2

Quality category 3 Chlorinated paraffins < 0.1 % and SVHC < 0.1 % Chlorinated paraffins < 0.1 % and SVHC < 0.1 % Quality category 4 (high)

Classification Fulfills quality category 4 requirements with chlorinated paraffins < 0.1 % and

SVHC < 0.1%.

### BNB – Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)

Version 2015

Criterion 1.1.6 Risks for the local environment

Overview table 4. Surface coatings on predominantly non-mineral surfaces (wood, metals, plastics) – line no. 44

Construction product type

Fire protection primers, fire protection coatings for cables, fire protection silicones for fillings, coatings, adhesives or sealings in interiors and exteriors with fire protection requirements.

Requirements Quality category 1 (low) Documentation and declaration of contained SVHC > 0.1 %.

> Quality category 2 Declaration of contained SVHC > 0.1 % and chlorinated paraffins,

PBB, PBDE, TCEP < 0.1 %.

Quality category 3 Declaration of contained SVHC > 0.1 % and chlorinated paraffins,

PBB, PBDE, TCEP < 0.1%.

Declaration of contained SVHC > 0.1 % and chlorinated paraffins, Quality category 4

PBB, PBDE, TCEP < 0.1%.

Quality category 5 (high) Declaration of contained SVHC > 0.1 % and chlorinated paraffins,

PBB, PBDE, TCEP < 0.1%.

Classification Fulfills the quality category 5 requirements as declaration of contained SVHC > 0.1 % and

chlorinated paraffins, PBB, PBDE, TCEP < 0.1 %.

Sustainability data sheet OTTOSEAL® S54 version: 2gb (13.03.2024 08:09 h)

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY

Tel.:+49 8684-908-0 · Fax: +49 8684-12-60

e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com



SEALING & BONDING

### BNB - Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)

Version 2015

product type

Criterion 1.1.6 Risks for the local environment

Overview table 6. Adhesives and sealants – line no. 8

Construction

6. Adhesives and sealants – line no. 8

Construction

Adhesives and sealants made of PU, SMP (silane-modified polymers), acrylate (including

dispersion adhesives) or silicone for punctiform and linear bonding and sealing in the interior,

including TGA.

**Requirements** Quality category 1 (low) Documentation, declaration of contained SVHC > 0.1 % and

declaration of biocidal agents (if used).

Quality category 2 Declaration of biocidal agents (if used) and declaration of contained

SVHC > 0.1 % and chlorinated paraffins < 0.1 %.

For PU adhesives additionally applies: GISCODE PU10 or PU20

and TCEP < 0.1%.

Quality category 3 Declaration of biocidal agents (if used) and declaration of contained

SVHC > 0.1 % and chlorinated paraffins < 0.1 %.

For PU adhesives additionally applies: GISCODE PU10 or PU20

and TCEP < 0.1 %.

Quality category 4 No amine- or oxime-interlacing silicones.

Additionally applies: RAL-UZ 123 or EMICODE® EC 1/EC 1 PLUS and chlorinated paraffins and declaration of biocidal agents (if used)

and declaration of contained SVHC > 0.1%.

For PU adhesives additionally applies: TCEP < 0.1 %.

Quality category 5 (high) No amine- or oxime-interlacing silicones.

Additionally applies: RAL-UZ 123 or EMICODE® EC 1/EC 1 PLUS and chlorinated paraffins < 0.1 % and declaration of biocidal agents

(if used) and declaration of contained SVHC > 0.1 %. For PU adhesives additionally applies: TCEP < 0.1 %.

Classification Fulfills the quality category 3 requirements because of declaration of biocidal agents

(if used) and declaration of contained SVHC > 0.1 % and chlorinated paraffins < 0.1 % .

Documentation documents

All the listed documents can be downloaded from www.otto-chemie.com

Technical data sheet
 Safety data sheet

3. Sustainability data sheet

4. Test certificates

5. Environmental product declaration

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: www.otto-chemie.com. Furthermore, the information in the documents accompanying the products is applicable.

Sustainability data sheet OTTOSEAL® S54 Page 4 version: 2gb (13.03.2024 08:09 h)

Hermann Otto GmbH  $\cdot$  Krankenhausstr. 14  $\cdot$  83413 Fridolfing, GERMANY

Tel.:+49 8684-908-0 · Fax: +49 8684-12-60 e-mail: info@otto-chemie.de · Internet: www.otto-chemie.com

