

OTTOCOLL®

A270

Sustainability data sheet

Inspections/authorisations



- French VOC-emission class A+

- Environmental Product Declarations (EPD)

Declaration number: EPD-DBC-20220147-IBF1-EN

Building certification system

QNG - Quality Seal for Sustainable Buildings

Version 1.3

Criterion	Avoiding harmful substances in building materials
Overview table	4. Adhesives and sealants - line 4.1
Building product group	Adhesives and sealants (acrylates and silicones) used on site indoors
Requirements	Product documentation and declaration of contained SVHC >0.1 % and chlorinated paraffins ≤0.1 % and declaration of biocidal active substances in silicones
Classification	Meets the requirements, as declaration of contained SVHC >0.1 % and chlorinated paraffins ≤0.1 % and declaration of biocidal active substances in silicones.

Criterion	ENV 1.2 Risks for the local environment	
Criteria matrix	line no. 11	
Product type	Sealing compounds, sealants, adhesives for dot and line-formed bonding of building components on the interior: - mechanically stressed joints - baseboards - door rails - support adhesive (raised or hollow floor) - ventilation ducts This refers to acrylic adhesives/bonding agents, silicone sealants, PU adhesives and silane-modified polymers (SMP).	
Requirements	Quality category 1 (low)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and bonus points SVHC $\leq 0.1\%$
	Quality category 2	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and bonus points SVHC $\leq 0.1\%$
	Quality category 3	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and EMICODE® EC 1 ^{PLUS} and bonus points SVHC $\leq 0.1\%$
	Quality category 4 (high)	GISCODE PU10, PU20, RS10, DA20, DSE20, DSA20, DSO20 or DH20 and EMICODE® EC 1 ^{PLUS} and bonus points SVHC $\leq 0.1\%$
Classification	Fulfills quality category 2 requirements with GISCODE DA20 and SVHC $\leq 0.1\%$.	

Criterion	ENV 1.2 Risks for the local environment	
Criteria matrix	line no. 13	
Product type	Adhesive for air tightness of facades inside and outside: e. g. PU, PU Hybrid, MS Polymer, SMP, acrylate, silicone.	
Requirements	Quality category 1 (low)	<0.1 % halogenated propellant and bonus points SVHC $\leq 0.1\%$
	Quality category 2	<0.1 % halogenated propellant and bonus points SVHC $\leq 0.1\%$
	Quality category 3	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 ^{PLUS} or VOC <1 % and bonus points SVHC $\leq 0.1\%$
	Quality category 4 (high)	Chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1 ^{PLUS} or VOC <1 % and bonus points SVHC $\leq 0.1\%$
Classification	Fulfills quality category 4 requirements with chlorinated paraffins (SCCPs + MCCPs + LCCPs) <0.1 % and halogenated propellant <0.1 % and VOC <1 % und SVHC $\leq 0.1\%$.	

Criterion	ENV 1.2 Risks for the local environment	
Criteria matrix	line no. 13	
Product type	Adhesive for air tightness of facades inside and outside: e.g. PU, PU Hybrid, MS Polymer, SMP or similar.	
Requirements	Quality category 1 (low)	<0.1 % halogenated propellant
	Quality category 2	<0.1 % halogenated propellant
	Quality category 3	Chlorinated paraffins <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1/EC 1 ^{PLUS} or VOC <1 %
	Quality category 4 (high)	Chlorinated paraffins <0.1 % and halogenated propellant <0.1 % and EMICODE® EC 1/EC 1 ^{PLUS} or VOC <1 %
Classification	Fulfills quality category 4 requirements with chlorinated paraffins <0.1 % and halogenated propellant <0.1 % and VOC <1 %.	

BNB – Bewertungssystem Nachhaltiges Bauen (Rating System for Sustainable Building)

Criterion	1.1.6 Risks for the local environment	
Overview table	6. Adhesives and sealants – line no. 9	
Construction product type	Adhesives and sealants for the airtightness of facades inside and outside: e.g. PU, PU hybrid, MS polymer, SMP, etc. for punctiform and linear bonding of components for the airtightness of facades, windows and external doors.	
Requirements	Quality category 1 (low)	Documentation and declaration of contained SVHC >0.1 %.
	Quality category 2	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 %. For PU adhesives additionally applies: TCEP <0.1 %.
	Quality category 3	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 %. For PU adhesives additionally applies: TCEP <0.1 %.
	Quality category 4	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 % and EMICODE® EC 1/EC 1 ^{PLUS} or VOC <10 g/l. For PU adhesives additionally applies: TCEP <0.1 %.
	Quality category 5 (high)	Declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 % and EMICODE® EC 1/EC 1 ^{PLUS} or VOC <10 g/l. For PU adhesives additionally applies: TCEP <0.1 %.
Classification	Fulfills the quality category 3 requirements as declaration of contained SVHC >0.1 % and chlorinated paraffins <0.1 %.	
Documentation documents	All the listed documents can be downloaded from www.otto-chemie.com 1. Technical data sheet 2. Safety data sheet 3. Sustainability data sheet 4. Test certificates 5. Environmental product declaration	

This information is based on our knowledge at the time of the compilation (see below). The current version can be viewed on our website at: www.otto-chemie.com. Furthermore, the information in the documents accompanying the products is applicable.
